



# EXCAVATORS

## COMPACT TIER 4 FINAL

Hyundai compact excavators deliver reliable power and performance with minimal downtime. Cabs are generous, to allow operators to be comfortable and productive longer. And every model is packed with standard features that increase productivity, reliability, comfort and safety.



### HX17AZ

**Net Power**  
16 hp (11.9 kW) at 2,400 rpm  
**Operating Weight**  
4,370 lb (1,980 kg)  
**Standard Bucket Capacity**  
0.05 yd<sup>3</sup> (0.04 m<sup>3</sup>)



### HX27AZ

**Net Power**  
24.4 hp (18.2 kW) at 2,400 rpm  
**Operating Weight**  
5,919 lb (2,685 kg)  
**Standard Bucket Capacity**  
0.14 yd<sup>3</sup> (0.11 m<sup>3</sup>)



### HX35AZ

**Net Power**  
24.2 hp (17.8 kW) at 2,200 rpm  
**Operating Weight**  
8,930 lb (4,050 kg)  
**Standard Bucket Capacity**  
0.14 yd<sup>3</sup> (0.11 m<sup>3</sup>)



### HX40A

**Net Power**  
37.7 hp (28.1 kW) at 2,200 rpm  
**Operating Weight**  
9,680 lb (4,390 kg)  
**Standard Bucket Capacity**  
0.14 yd<sup>3</sup> (0.11 m<sup>3</sup>)



### HX48AZ

**Net Power**  
37.7 hp (28.1 kW) at 2,200 rpm  
**Operating Weight**  
11,200 lb (5,080 kg)  
**Standard Bucket Capacity**  
0.20 yd<sup>3</sup> (0.15 m<sup>3</sup>)



### HX55A CR

**Net Power**  
45 hp (33.6 kW) at 2,400 rpm  
**Operating Weight**  
12,460 lb (5,650 kg)  
**Standard Bucket Capacity**  
0.20 yd<sup>3</sup> (0.15 m<sup>3</sup>)



### HX60A

**Net Power**  
65 hp (48.5 kW) at 2,400 rpm  
**Operating Weight**  
13,580 lb (6,160 kg)  
**Standard Bucket Capacity**  
0.24 yd<sup>3</sup> (0.18 m<sup>3</sup>)



### HX85A

**Net Power**  
65 hp (48.5 kW) at 2,400 rpm  
**Operating Weight**  
19,026 lb (8,630 kg)  
**Standard Bucket Capacity**  
0.33 yd<sup>3</sup> (0.25 m<sup>3</sup>)

### HX90A

**Net Power**  
65 hp (48.5 kW) at 2,400 rpm  
**Operating Weight**  
20,040 lb (9,090 kg)  
**Standard Bucket Capacity**  
0.33 yd<sup>3</sup> (0.25 m<sup>3</sup>)

## COMPACT TIER 4 FINAL



### R17Z-9A

**Net Power**  
15.8 hp (11.8 kW) at 2,300 rpm  
**Operating Weight**  
3,920 lb (1,780 kg)  
**Standard Bucket Capacity**  
0.05 yd<sup>3</sup> (0.04 m<sup>3</sup>)



### R25Z-9AK

**Net Power**  
23.2 hp (17.3 kW) at 2,350 rpm  
**Operating Weight**  
5,360 - 5,640 lb (2,431 - 2,558 kg)  
**Standard Bucket Capacity**  
0.09 - 0.24 yd<sup>3</sup> (0.07 - 0.18 m<sup>3</sup>)



### R30Z-9AK

**Net Power**  
23.2 hp (17.3 kW) at 2,350 rpm  
**Operating Weight**  
6,625 lb (3,005 kg)  
**Standard Bucket Capacity**  
0.09 yd<sup>3</sup> (0.08 m<sup>3</sup>)



### R35Z-9A

**Net Power**  
23.7 hp (17.7 kW) at 2,200 rpm  
**Operating Weight**  
8,470 lb (3,840 kg)  
**Standard Bucket Capacity**  
0.14 yd<sup>3</sup> (0.11 m<sup>3</sup>)



### R55-9A

**Net Power**  
65.1 hp (48.5 kW) at 2,400 rpm  
**Operating Weight**  
12,570 lb (5,750 kg)  
**Standard Bucket Capacity**  
0.24 yd<sup>3</sup> (0.18 m<sup>3</sup>)



### R60CR-9A

**Net Power**  
63 hp (47 kW) at 2,200 rpm  
**Operating Weight**  
13,450 lb (6,100 kg)  
**Standard Bucket Capacity**  
0.9 - 0.24 yd<sup>3</sup> (0.07 - 0.18 m<sup>3</sup>)



### R80CR-9A

**Net Power**  
65.1 hp (48.5 kW) at 2,400 rpm  
**Operating Weight**  
19,290 lb (8,750 kg)  
**Standard Bucket Capacity**  
0.18 - 0.37 yd<sup>3</sup> (0.14 - 0.28 m<sup>3</sup>)

# EXCAVATORS

## CRAWLER TIER 4 FINAL

Built with automotive-style comfort and convenience features and trusted components designed for the rigors of construction, Hyundai crawler excavators are backed by our expanding dealer network and one of the industry's best warranties. Five years of Hyundai Connect, Hyundai's proprietary remote management system further protects your investment and helps you keep your equipment productive for the long haul.



### HX130A LCR

Net Power  
72 hp (54 kW) at 2,200 rpm  
Operating Weight  
29,649 lb (13,445 kg)  
Standard Bucket Capacity  
0.65 yd<sup>3</sup> (0.50 m<sup>3</sup>)



### HX140A L

Net Power  
131 hp (98 kW) at 2,200 rpm  
Operating Weight  
33,580 lb (15,230 kg)  
Standard Bucket Capacity  
0.80 yd<sup>3</sup> (0.61 m<sup>3</sup>)



### HX145A LCR

Net Power  
131 hp (98 kW) at 2,200 rpm  
Operating Weight  
34,020 lb (15,430 kg)  
Standard Bucket Capacity  
0.80 yd<sup>3</sup> (0.61 m<sup>3</sup>)



### HX160A L

Net Power  
152 hp (113 kW) at 2,200 rpm  
Operating Weight  
39,010 lb (17,695 kg)  
Standard Bucket Capacity  
0.80 yd<sup>3</sup> (0.72 m<sup>3</sup>)



### HX180A L

Net Power  
152 hp (113 kW) at 2,200 rpm  
Operating Weight  
40,570 lb (18,402 kg)  
Standard Bucket Capacity  
0.95 yd<sup>3</sup> (0.73 m<sup>3</sup>)



### HX210A L

Net Power  
170 hp (127 kW) at 2,200 rpm  
Operating Weight  
50,460 lb (22,890 kg)  
Standard Bucket Capacity  
1.2 yd<sup>3</sup> (1.0 m<sup>3</sup>)

## CRAWLER TIER 4 FINAL



### HX220A L

Net Power  
170 hp (127 kW) at 2,200 rpm  
Operating Weight  
50,265 - 54,516 lb  
(22,800 - 24,728 kg)  
Standard Bucket Capacity  
1.20 yd<sup>3</sup> (0.92 m<sup>3</sup>)



### HX220A LR

Net Power  
170 hp (127 kW) at 2,200 rpm  
Operating Weight  
56,040 lb (25,420 kg)  
Standard Bucket Capacity  
0.68 yd<sup>3</sup> (0.52 m<sup>3</sup>)



### HX235A LCR

Net Power  
170 hp (127 kW) at 2,200 rpm  
Operating Weight  
52,910 - 54,140 lb  
(24,000 - 24,557 kg)  
Standard Bucket Capacity  
0.67 - 1.75 yd<sup>3</sup> (0.51 - 1.34 m<sup>3</sup>)



### HX260A L

Net Power  
227 hp (169 kW) at 2,000 rpm  
Operating Weight  
59,520 - 61,530 lb  
(27,000 - 27,910 kg)  
Standard Bucket Capacity  
1.53 yd<sup>3</sup> (1.17 m<sup>3</sup>)



### HX300A L

Net Power  
255 hp (190 kW) at 2,200 rpm  
Operating Weight  
72,200 lb (32,750 kg)  
Standard Bucket Capacity  
1.66 - 2.42 yd<sup>3</sup> (1.27 - 1.85 m<sup>3</sup>)



### HX300A LR

Net Power  
255 hp (190 kW) at 2,200 rpm  
Operating Weight  
74,050 lb (33,590 kg)  
Standard Bucket Capacity  
0.68 yd<sup>3</sup> (0.52 m<sup>3</sup>)



### HX350A L

Net Power  
304 hp (227 kW) at 2,100 rpm  
Operating Weight  
77,184 - 83,330 lb  
(35,010 - 37,800 kg)  
Standard Bucket Capacity  
1.88 yd<sup>3</sup> (1.44 m<sup>3</sup>)



### HX355A LCR

Net Power  
258 hp (192 kW) at 2,200 rpm  
Operating Weight  
78,483 - 79,807 lb  
(35,600 - 36,200 kg)  
Standard Bucket Capacity  
1.66 yd<sup>3</sup> (1.27 m<sup>3</sup>)

# EXCAVATORS

## CRAWLER TIER 4 FINAL



### HX380A L

**Net Power**  
359 hp (268 kW) at 2,100 rpm  
**Operating Weight**  
88,053 lb (39,940 kg)  
**Standard Bucket Capacity**  
2.12 yd<sup>3</sup> (1.62 m<sup>3</sup>)



### HX480A L

**Net Power**  
395 hp (295 kW) at 2,100 rpm  
**Operating Weight**  
111,752 - 116,095 lb  
(50,690 - 52,660 kg)  
**Standard Bucket Capacity**  
2.88 yd<sup>3</sup> (2.2 m<sup>3</sup>)



### HX520A L

**Net Power**  
395 hp (295 kW) at 2,100 rpm  
**Operating Weight**  
120,704 lb (54,750 kg)  
**Standard Bucket Capacity**  
3.41 yd<sup>3</sup> (2.6 m<sup>3</sup>)



### HX800A L

**Net Power**  
528 hp (389 kW) at 2,100 rpm  
**Operating Weight**  
180,999 lb (82,100 kg)  
**Standard Bucket Capacity**  
5.1 yd<sup>3</sup> (3.9 m<sup>3</sup>)



### HX1000A L

**Net Power**  
629 hp (469 kW) at 2,000 rpm  
**Operating Weight**  
220,282 lb (100,128 kg)  
**Standard Bucket Capacity**  
7.06 - 8.89 yd<sup>3</sup> (5.4 - 6.8 m<sup>3</sup>)

## WHEELED TIER 4 FINAL



### HW100A

**Net Power**  
100 hp (73 kW) at 2,000 rpm  
**Operating Weight**  
23,589 lb (10,699 kg)  
**Maximum Travel Speed**  
23.2 mph (37 km/h)



### HW140A

**Net Power**  
170 hp (127 kW) at 2,200 rpm  
**Operating Weight**  
35,053 lb (15,900 kg)  
**Maximum Travel Speed**  
24.2 mph (39 km/h)



### HW160A

**Net Power**  
170 hp (127 kW) at 2,200 rpm  
**Operating Weight**  
38,910 Lb (17,650 kg)  
**Maximum Travel Speed**  
24.2 mph (39 km/h)



### HW170A CR

**Net Power**  
170 hp (127 kW) at 2,200 rpm  
**Operating Weight**  
41,513 Lb (18,820 kg)  
**Maximum Travel Speed**  
24.2 mph (39 km/h)



### HW210A

**Net Power**  
170 hp (127 kW) at 2,200 rpm  
**Operating Weight**  
46,690 Lb (21,180 kg)  
**Maximum Travel Speed**  
24.2 mph (39 km/h)



### R55W-9A

**Net Power**  
66.9 hp (49.9 kW) at 2,400 rpm  
**Operating Weight**  
12,240 lb (5,552 kg)  
**Maximum Travel Speed**  
18.6 mph (30 km/h)

# WHEEL LOADERS

## Z-BAR AND XT TIER 4 FINAL

Hyundai wheel loaders are available in our standard Z-bar linkage configuration, with XT (extended-reach) versions available for applications that require greater reach and higher dump heights. Whatever your need, there's a Hyundai wheel loader with the right combination of power, capacity and efficiency to get the job done.

### HL930A



Net Power  
130 hp (97 kW) at 2,200 rpm  
Operating Weight  
25,595 lb (11,610 kg)  
Standard Bucket Capacity  
2.1 - 2.5 yd<sup>3</sup> (1.6 - 1.9 m<sup>3</sup>)



### HL930A XT

Net Power  
130 hp (97 kW) at 2,200 rpm  
Operating Weight  
25,795 lb (11,700 kg)  
Standard Bucket Capacity  
2.1 - 2.5 yd<sup>3</sup> (1.6 - 1.9 m<sup>3</sup>)

### HL940A



Net Power  
154 hp (115 kW) at 2,200 rpm  
Operating Weight  
29,985 lb (13,601 kg)  
Standard Bucket Capacity  
3 yd<sup>3</sup> (2.3 m<sup>3</sup>)



### HL940A XT

Net Power  
154 hp (115 kW) at 2,200 rpm  
Operating Weight  
30,560 lb (13,862 kg)  
Standard Bucket Capacity  
3 yd<sup>3</sup> (2.3 m<sup>3</sup>)

### HL955A



Net Power  
197 hp (147 kW) at 2,200 rpm  
Operating Weight  
35,490 lb (16,098 kg)  
Standard Bucket Capacity  
3.7 yd<sup>3</sup> (2.8 m<sup>3</sup>)



### HL955A HD

Net Power  
197 hp (147 kW) at 2,200 rpm  
Operating Weight  
36,350 lb (15,800 - 16,490 kg)  
Standard Bucket Capacity  
3.7 yd<sup>3</sup> (2.8 m<sup>3</sup>)



### HL955A HDXT



Net Power  
197 hp (147 kW) at 2,200 rpm  
Operating Weight  
36,355 lb (16,490 kg)  
Standard Bucket Capacity  
3.7 yd<sup>3</sup> (2.8 m<sup>3</sup>)

### HL955A XT

Net Power  
197 hp (147 kW) at 2,200 rpm  
Operating Weight  
36,355 lb (16,490 kg)  
Standard Bucket Capacity  
3.7 yd<sup>3</sup> (2.8 m<sup>3</sup>)

## Z-BAR AND XT TIER 4 FINAL

### HL960A



Net Power  
222 hp (166 kW) at 2,200 rpm  
Operating Weight  
43,720 lb (19,831 kg)  
Standard Bucket Capacity  
4.3 yd<sup>3</sup> (3.3 m<sup>3</sup>)



### HL960A HD

Net Power  
222 hp (166 kW) at 2,200 rpm  
Operating Weight  
42,880 lb (19,450 kg)  
Standard Bucket Capacity  
4.3 yd<sup>3</sup> (3.3 m<sup>3</sup>)



### HL960A HDXT

Net Power  
222 hp (166 kW) at 2,100 rpm  
Operating Weight  
44,710 lb (20,280 kg)  
Standard Bucket Capacity  
4.3 yd<sup>3</sup> (3.3 m<sup>3</sup>)



### HL960A XT

Net Power  
222 hp (166 kW) at 2,200 rpm  
Operating Weight  
44,160 lb (20,030 kg)  
Standard Bucket Capacity  
4.3 yd<sup>3</sup> (3.3 m<sup>3</sup>)



### HL965

Net Power  
269 hp (198 kW) at 2,100 rpm  
Operating Weight  
45,700 lb (20,730 kg)  
Standard Bucket Capacity  
4.7 yd<sup>3</sup> (3.6 m<sup>3</sup>)



### HL970A

Net Power  
322 hp (240 kW) at 2,100 rpm  
Operating Weight  
54,455 lb (24,700 kg)  
Standard Bucket Capacity  
5.5 yd<sup>3</sup> (4.2 m<sup>3</sup>)



### HL970A XT

Net Power  
322 hp (240 kW) at 2,100 rpm  
Operating Weight  
55,120 lb (25,000 kg)  
Standard Bucket Capacity  
5.5 yd<sup>3</sup> (4.2 m<sup>3</sup>)



### HL975

Net Power  
331 hp (247 kW) at 2,100 rpm  
Operating Weight  
58,430 lb (26,500 kg)  
Standard Bucket Capacity  
6.3 yd<sup>3</sup> (4.8 m<sup>3</sup>)

## Z-BAR AND XT TIER 4 FINAL



### HL975 XT

Net Power  
331 hp (247 kW) at 2,100 rpm  
Operating Weight  
60,175 lb (27,295 kg)  
Standard Bucket Capacity  
6.3 yd<sup>3</sup> (4.8 m<sup>3</sup>)



### HL980A

Net Power  
351 hp (262 kW) at 2,200 rpm  
Operating Weight  
69,120 lb (31,352 kg)  
Standard Bucket Capacity  
7.3 yd<sup>3</sup> (5.6 m<sup>3</sup>)



### HL980A XT

Net Power  
351 hp (262 kW) at 2,200 rpm  
Operating Weight  
69,450 lb (31,502 kg)  
Standard Bucket Capacity  
7.3 yd<sup>3</sup> (5.6 m<sup>3</sup>)

### HL985A

Net Power  
420 hp (321 kW) at 2,100 rpm  
Operating Weight  
77,935 lb (35,350 kg)  
Standard Bucket Capacity  
9.2 yd<sup>3</sup> (7.0 m<sup>3</sup>)



### HA30

Net Power  
362 hp (270 kW) at 2,100 rpm  
Operating Weight  
51,147 lb (23,200 kg)  
Payload  
61,730 lb (28,000 kg)



### HA45

Net Power  
483 hp (360 kW) at 2,100 rpm  
Operating Weight  
66,359 lb (30,100 kg)  
Payload  
90,390 lb (41,000 kg)

## TOOL MASTER TIER 4 FINAL

If you need the versatility of a tool-carrier, Hyundai offers three models with our Tool Master boom design, with parallel linkage for increased lifting capacity, improved load stability, rapid dumping capability and enhanced visibility.



### HL930A TM

Net Power  
130 hp (97 kW) at 2,200 rpm  
Operating Weight  
26,370 lb (11,960 kg)  
Standard Bucket Capacity  
2.5 yd<sup>3</sup> (1.9 m<sup>3</sup>)



### HL940A TM

Net Power  
154 hp (115 kW) at 2,200 rpm  
Operating Weight  
30,645 lb (13,900 kg)  
Standard Bucket Capacity  
2.6 - 3.0 yd<sup>3</sup> (2.0 - 2.3 m<sup>3</sup>)



### HL955A TM

Net Power  
197 hp (147 kW) at 2,200 rpm  
Operating Weight  
36,380 lb (16,500 kg)  
Standard Bucket Capacity  
3.7 yd<sup>3</sup> (2.3 m<sup>3</sup>)

# ARTICULATED DUMP TRUCKS

## TIER 4 FINAL

From the front bumper to the tail end of the dump body, Hyundai ADTs are built to deliver a payload of productivity and efficiency, comfort, serviceability and safety. Like other Hyundai equipment, they are loaded with standard features and technologies that perform day in and day out under the toughest conditions.



### HA30

Net Power  
362 hp (270 kW) at 2,100 rpm  
Operating Weight  
51,147 lb (23,200 kg)  
Payload  
61,730 lb (28,000 kg)



### HA45

Net Power  
483 hp (360 kW) at 2,100 rpm  
Operating Weight  
66,359 lb (30,100 kg)  
Payload  
90,390 lb (41,000 kg)

# COMPACT LOADERS

## TIER 4 FINAL

Whether a compact track loader or skid steer is your entry into construction, landscaping or other applications or whether they are the extra workhorses you need tackling smaller tasks on big jobs, Hyundai's compact track loaders and skid steer loader are ready to dig, lift, load, carry and more.



### HS120V

Net Power  
69.7 hp (52 kW) at 2,400 rpm  
Operating Weight  
8,481 lb (3,847 kg)  
Rated Operating Capacity  
2,690 lb (1,220 kg)



### HT100V

Net Power  
69.7 hp (52 kW) at 2,400 rpm  
Operating Weight  
9,755 lb (4,425 kg)  
Rated Operating Capacity  
2,300 lb (1,043 kg)



### HT38

Gross Power  
102.6 hp (76.5 kW) at 2,400 rpm  
Operating Weight  
12,785 lb (5,799 kg)  
Rated Operating Capacity  
3,806 lb (1,727 kg)

# DOZERS

## TIER 4 FINAL

Hyundai offers two crawler dozer models in low-ground-pressure and XL configurations to help you tackle a wide range of earthmoving and material-handling applications. Among the many standard features are a six-way dozer blade, rearview camera, 8-inch display, high-illumination LED lights, and piping for a ripper.



### HD100 LGP

Rated Power  
115.3 hp (86 kW) at 2,200 rpm  
Operating Weight  
24,692 lb (11,200 kg)  
Maximum Traction Force (ISO)  
35,296 lbf (16,010 kgf)



### HD100 XL

Rated Power  
115.3 hp (86 kW) at 2,200 rpm  
Operating Weight  
23,589 lb (10,700 kg)  
Maximum Traction Force (ISO)  
35,296 lbf (16,010 kgf)



### HD130 LGP

Rated Power  
157 hp (117 kW) at 2,200 rpm  
Operating Weight  
33,730 lb (15,300 kg)  
Maximum Traction Force (ISO)  
48,501 lbf (22,000 kgf)



### HD130 XL

Rated Power  
157 hp (117 kW) at 2,200 rpm  
Operating Weight  
31,967 lb (14,500 kg)  
Maximum Traction Force (ISO)  
48,501 lbf (22,000 kgf)

# SPECIAL EQUIPMENT

When you buy a log loader or road builder model from Hyundai, you get more than a great machine purpose-built for the rigors of working in timber country. You also get the built-in Hyundai DNA, including ease of maintenance and serviceability, productivity and performance, comfort, and safety features that help you move more timber, faster. That same principle applies to our material handler, which can be customized for use in a variety of specialized applications.

## LOG LOADERS



### HX220LL

Net Power  
163 hp (121.4 kW) at 1,800 rpm  
Operating Weight  
68,784 lb (31,200 kg)



### HX300LL

Net Power  
266.6 hp (196 kW) at 1,800 rpm  
Operating Weight  
82,673 lb (37,500 kg)

## ROAD BUILDERS



### HX220RB

Net Power  
163 hp (121.4 kW) at 1,800 rpm  
Operating Weight  
65,918 lb (29,900 kg)



### HX300RB

Net Power  
266.6 hp (196 kW) at 1,800 rpm  
Operating Weight  
83,012 lb (37,200 kg)

## MATERIAL HANDLER



### HW250A MH

Net Power  
170 hp (127 kW) at 2,200 rpm  
Operating Weight  
58,422 lb (26,400 kg)  
Maximum Travel Speed  
21.7 mph (35 km/h)

# MEMO

# Easy to Own, Easy to Operate



## BACKED BY HD CONSTRUCTION EQUIPMENT

### **Built to perform**

All Hyundai equipment is built to perform, day in and day out, to meet our customers toughest expectations and quality standards.

### **North American dealer network**

Hyundai construction equipment is sold and serviced through a growing network of more than 80 dealerships operating from nearly 200 locations across the United States and Canada.

### **Support**

When you purchase a Hyundai machine, you know your investment is as solid as the steel on our buckets and booms. You can count on the Hyundai difference.

- Products packed with value, with more standard features on every machine.
- Industry-leading standard warranty of 3 years or 3,000 hours, plus a 5-year, 10,000-hour structural warranty, with the option to add Hyundai Extend, an extended-warranty program.
- Knowledgeable, trained and experienced service personnel, backed by our solutions-focused field support team.
- Parts support, with an exceptional fill rate for parts orders submitted by our dealers on behalf of customers like you to our warehouses in suburban Atlanta and Mississauga, Ontario.

# HYUNDAI

6100 Atlantic Blvd., Norcross, GA 30071  
TEL (678) 823-7777 FAX (678) 823-7778  
na.HD-HyundaiCE.com



Printed in U.S.A.

Full-Line-CL-SP 12/2025v9